

MV-SC6016C-00C

1.6 MP Color Smart Camera



Introduction

MV-SC6016C-00C smart camera is developed based on high-performance embedded platform with strong calculation performance. It integrates VM functions and AI deep learning algorithm, and can use more than 140 algorithms. It adopts multiple interfaces for supporting external light source, display, mouse, etc.

Available Models

- MV-SC6016C-00C-NNN
- MV-SC6016C-00C-NNN/V2


Key Features

- Adopts AI deep learning algorithm to achieve OCR, object recognition, defect detection, etc.
- Integrates VM functions, and supports more than 140 algorithms.
- Adopts multiple interfaces, and supports multiple-channel I/O, light source, display, etc.
- Adopts high-performance CPU with faster calculation performance and high efficiency.
- Supports multiple communication protocols.
- Supports indicators displaying device status for easy debugging and maintenance.
- Supports ingress protection IP67.

Applicable Industry

Consumer electronics, food and pharmaceutical, packaging, positioning and grabbing, etc.

Dimension



Specification

Model	MV-SC6016C-00C-NNN	MV-SC6016C-00C-NNN/V2
Tool		
Function module	Vision Master Platform (include deep learning module)	
Communication protocol	TCP, UDP, MODBUS, Serial Port, PROFINET, EtherNet/IP, Fins, MC, FTP, etc.	
Camera		
Sensor type	CMOS, global shutter	
Pixel size	3.45 μm × 3.45 μm	
Sensor size	1/2.9"	
Resolution	1408 × 1024	
Max. frame rate	60 fps	120 fps
Gain	0 dB to 15 dB	
Exposure time	16 μs to 1 sec	25 μs to 1 sec
Pixel format	Mono 8, RGB 8	
Mono/color	Color	
Platform		
Memory	8 GB	
Storage	64 GB	
Electrical feature		
Data interface	Gigabit Ethernet (1000 Mbit/s)	
Digital I/O	17-pin M12 connector provides power and I/O, including opto-isolated input × 2 (Line 0/1), opto-isolated output × 2 (Line 4/5), configurable non-isolated input/output × 2 (Line 2/3), RS-232 × 1, and light source output (max. 30 W) × 1	
Extended interface	VGA × 1, and USB host × 1	
Power supply	24 VDC	
Power consumption	Approx. 12 W @ 24 VDC (without external light source) Approx. 42 W @ 24 VDC (with external light source)	
Mechanical		
Lens mount	C-mount	
Lens cap	Transparent lens cap	
Light source	Not included	
Indicator	Power indicator (PWR), network indicator (LNK), status indictor (STS), and user-defined indicator (U1/U2)	
Dimension	116.3 mm × 68.6 mm × 101.8 mm (4.6" × 2.7" × 4.0")	
Weight	Approx. 530 g (1.2 lb.)	
Ingress protection	IP67 (under proper installation of waterproof lens cap)	
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: −30 °C to 70 °C (−22 °F to 158 °F)	
Humidity	20% RH to 95% RH (no condensation)	
General		
Certification	CE, KC	