

# SPP-L3000

3 inch Mobile Label Printer



Ticketing



Stadium & Arenas



Logistics



Retail

# Industrial and Powerful



### Premium-Level Performance

- Fully compatible with market-leading programming languages
- Interchangeable programming language without re-setting the mode
- Fast data processing and printing speed up to 5 ips (127 mm/sec)
- Smart Media Detection™
- Anywhere Anyfont™ (Unicode) removes the need to write multiple code pages for each language



### Seamless Mobility

- Simultaneously connects both Bluetooth 4.1 (MFi certified) and Dual-band WLAN (2.4GHz and 5GHz)
- Compatible with all major operating systems including Android™, iOS™ and Windows®
- Supports Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- SoftAP - Simple Wi-Fi set up to a mobile device
- Smart Connection™ mobile app - Easy switching from SoftAP to Infrastructure mode



### Enhanced optimization for field service

- Compact, ergonomic and light-weight (694g)
- 2.1 m / 7 ft. drop rate
- IP54 (Printer only) water and dust proof
- Various accessories and connectivity ports
- Easy to set up the printer status by LCD and control button
- Visual battery status
- Embedded peeler and paper guide

# SPP-L3000

3 inch Mobile Label Printer

8x **No.1** MOBILE RECEIPT PRINTER MANUFACTURER



Reported by  
Chunichisha

## Specifications

### Printer Specifications

#### Print Method

Direct Thermal

#### Print Speed

Up to 5 ips (127 mm/sec - Liner, Linerless)  
12.5% pattern

#### Print Resolution

203 dpi

#### Print Width

Up to 72 mm

#### Sensing

Paper End  
Gap  
Black Mark  
Paper Cover Open  
Label Presence

### Media Characteristics

#### Media Type

Label, Linerless (Optional)

#### Media Width

25 ~ 80 mm

#### Media Roll Diameter

Up to 66 mm

#### Media Thickness

0.07 ~ 0.15 mm

#### Media Inner Core

19mm, 12mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (WxDxH)

119.0 x 159.0 x 79.0 mm  
(4.67 x 6.26 x 3.12 inch)

#### Weight

Including battery: 694 g (1.53 lbs.)  
Paper: 257 g (0.57 lbs.)

#### Electrical

7.3 V Li-ion, 2600 mAh,  
Rechargeable Charging time: Up to 2.5 hrs  
EnergyStar Certified

#### Peeler

Supported

#### Paper Guide

Yes (Inner core: 19mm)

#### Display

FSTN LCD (200 x 100 pixels)

### Performance Characteristics

#### Memory

128 MB SDRAM, 256 MB Flash  
256 MB SDRAM, 512 MB Flash (Optional)

#### Interface

Standard: USB V2.0 HS + Serial  
Optional: USB V2.0 HS + Serial + Bluetooth<sup>1</sup> /  
WLAN<sup>2</sup> / Dual Bluetooth<sup>1</sup> + WLAN<sup>2</sup>

Bluetooth<sup>1</sup>: V4.1 Classic & LE

WLAN<sup>2</sup>: 802.11a/b/g/n (Infrastructure, Ad-hoc,  
Wi-Fi Direct, SoftAP) - WEP40/104,  
WPA1/2(PSK, EAP)

\* Easy Bluetooth Pairing™ via NFC

### Environment Characteristics

#### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

#### Humidity

Operating: 10 ~ 80% RH

#### Sealing

IP54

#### Drop Rate

2.1 m (7 ft.)

### Software

#### Emulation

SLCS, BPL-Z™ (ZPLII), BPL-C™ (CPCL)

#### Driver / Utility

Windows Driver (Europlus / Seagull),  
Linux / Mac CUPS Driver, Virtual COM USB Driver,  
Utility Program, LabelArtist-II™, Bartender UL,  
OPOS / JPOS Driver

#### SDK / Plugin

Android / iOS / Windows SDK, Linux SDK,  
Chrome SDK, Xamarin SDK, Cordova Plugin

#### Application

Label Artist™ Mobile (Android, iOS),  
mPrint App (iOS), mPrint Server (Windows, iOS)

#### MDM

BIXOLON Profile Manager  
- XPM™, XCM™ (Windows, Android)

### Fonts / Graphics / Symbologies

#### Fonts

10 SLCS / One SLCS / 16 BPL-Z™ / One BPL-Z™ /  
7 BPL-C™ / 23 Code Page /  
Unicode supported  
(UTF-8, UTF-16LE, UTF-16BE)

#### Graphics

Supporting user-defined fonts, graphics,  
formats, layouts, and logos

#### Barcode Symbologies

1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8, Industrial 2-of-5,  
Interleaved 2-of-5, Logmars, MSI, Plessey,  
Postnet, GS1 DataBar (RSS-14),  
Standard 2-of-5, UPC / EAN extensions,  
UPC-A, UPC-E, IMB  
2D: Aztec, Codablock, Code 49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR code, TLC 39

### Accessories

#### Standard Accessories

Belt Strap, Battery Pack, SMPS, Power Cord,  
Paper Disk (Inner core : 12mm)

#### Optional Accessories

Smart Battery, Shoulder Strap,  
Single Battery Charger, Quad Battery Charger,  
Serial/USB Cable, Fixed Serial/USB Cable,  
RAM mount Vehicle-Holder, Vehicle Charger

### Supplies

Compatible with B-linerless™ BIXOLON's flexible  
and ecological linerless label consumables